



02-02-00

A

TAROLLI, SUNDHEIM, COVELL, TUMMINO & SZABO L.L.P.

1111 Leader Building
Cleveland, Ohio 44114

(216) 621-2234

PATENT

Attorney Docket No. TRW(TE)4170

Assistant Commissioner for Patents
Washington, D.C. 20231

NEW APPLICATION TRANSMITTAL

Transmitted herewith for filing is the patent application of Inventor(s): Roger A. McCurdy

For (title): **METHOD AND APPARATUS FOR CONTROLLING AN ACTUATABLE
OCCUPANT PROTECTION DEVICE USING AN ULTRASONIC SENSOR**

Enclosed are:

1. Papers Required for Filing Date Under 37 CFR 1.53(b):

- 29 Pages of specification
- 1 Pages Abstract
- 11 Pages of claims
- 4 Sheets of drawing
- ☒ formal (Figs. 1-4)
- ☐ informal

In addition to the above papers there is also attached:
(1 pg.); and ELEVEN (11) References.

An executed Information Disclosure Statement (2 pgs.); PTO-Form 1449

CERTIFICATION UNDER 37 CFR 1.10

I hereby certify that this New Application Transmittal and the documents referred to as enclosed therein are being deposited with the United States Postal Service on this date February 1, 2000 in an envelope as "Express Mail Post Office to Addressee" Mailing Label Number EJ-704501307US addressed to the: Assistant Commissioner for Patents, Washington D.C.

Anita J. Galo

(Type or print name of person mailing paper)

 (Signature of person mailing paper)

2. **Declaration or oath:**

- ☒ Enclosed (Executed)
☐ Not Enclosed.

3. **Language:**

- ☒ English
☐ Non-English
☐ A verified English translation of the
 ☐ specification and claims
 ☐ declaration
is attached.

4. **Assignment:**

- ☒ An assignment of the invention to TRW Inc.

☒ is attached.

☐ will follow

5. **Certified Copy:**

Certified copy (ies) of application (s)

(Country) (Appln. No.) (Filed)

(Country) (Appln. No.) (Filed)

(Country) (Appln. No.) (Filed)

from which priority is claimed

- ☐ is attached
☐ will follow

6. **Fee Calculation:**
(Small entity filing fee is 50% normal fee)

CLAIMS AS FILED						
Number Filed	Number Extra		Rate		Basic Fee	
					\$ 690.00	
Total Claims	22	-20 =	2	X	\$ 18.00	36.00
Independent Claims	5	- 3 =	2	X	\$ 78.00	156.00
Multiple dependent claim(s), if any			0	+	\$260.00	0.00

- ☐ Amendment canceling extra claims enclosed
- ☐ Amendment deleting multiple dependencies enclosed
- ☐ Fee for extra claims is not being paid at this time

Filing Fee Calculation \$882.00

7. **Small Entity Statement**

- ☐ Verified statement that this is a filing by a **small entity** under 37 CFR 1.9 and 1.27
(Must be enclosed to get small entity filing fee reduction)

8. **Fee Payment Being Made At This Time:**

Enclosed:

- ☒ basic filing fee \$882.00
- ☒ assignment recordal fee \$ 40.00
- ☐ for processing an application with a specification in a non-English language \$
- Total fees enclosed \$922.00

9. **Method of Payment Fees:**

- ☒ check in the amount of \$ 922.00 enclosed.

☒ The Commissioner is hereby authorized to charge any **DEFICIENCY** in the filing fees for this application to our Deposit Account No. 20-0090.

10. **Instructions As to Overpayment:**

- ☒ refund

TAROLLI, SUNDHEIM, COVELL,
TUMMINO & SZABO L.L.P.
1111 LEADER BUILDING
526 SUPERIOR AVENUE
CLEVELAND, OHIO 44114-1400
Tel. No. (216) 621-2234
Fax No. (216) 621-4072

Barry L. Tummino
SIGNATURE OF ATTORNEY, REG. NO. 29,709

Barry L. Tummino
Type or print name of attorney

ST-704501307US

I hereby certify that this paper or fee is being deposited with the U. S. Postal Service "Express Mail" service to "Addressee" serves under 37 C.F.R. 1.101 (b) as indicated below and is addressed to the Commissioner of Patents and Trademarks, Washington, D. C. 20530.

PATENT

Feb 1, 2000

Date of Deposit

Anita J. Galo

Signature of Person Mailing Paper or Fee

Anita J. Galo

Name of Person Signing

02/01/2000

Date of Mailing

METHOD AND APPARATUS FOR CONTROLLING AN ACTUATABLE OCCUPANT PROTECTION DEVICE USING AN ULTRASONIC SENSOR

Technical Field

The present invention relates to an apparatus and
5 method for controlling an actuatable occupant
protection device. More particularly, the present
invention relates to a method and apparatus for
controlling an actuatable occupant protection device
using an ultrasonic sensor in combination with at least
10 one other crash sensor.

Background of the Invention

Actuatable occupant restraint systems, such as air
bags and seat belt pretensioners, are well known in the
art. Such restraint systems include one or more
15 collision sensing devices, such as for sensing vehicle
crash acceleration (e.g., vehicle deceleration). An
air bag restraint system further includes an
electrically actuatable igniter, referred to as a
squib. When the collision sensing device senses a

deployment crash event, an electrical current of sufficient magnitude and duration is passed through the squib to ignite the squib. When ignited, the squib initiates the flow of inflation fluid into an air bag from a source of inflation fluid, as is known in the art.

Occupant protection systems utilize a variety of crash sensing devices, which may be either mechanical or electrical in nature. For example, some occupant protection systems include one or more accelerometers that sense vehicle crash acceleration and provides a signal indicative thereof. Systems having an accelerometer further include additional circuitry (e.g., a controller) for monitoring the output of the accelerometer. The accelerometer is operatively connected to the controller, which may be a microcomputer, that discriminates between a deployment and a non-deployment crash event by applying a predetermined crash algorithm to the acceleration signal. When a deployment crash event is determined to be occurring, the controller actuates the restraint.

Air bag restraint systems also are known to require more than one sensor for detection of a deployment crash event. Often, the plural sensors are

arranged in a voting scheme in which all the sensors must "agree" that a deployment crash event is occurring before restraint actuation is initiated. In certain known arrangements having plural sensors, the second
5 sensor is referred to as a "safing sensor." Air bag actuation occurs only if the first sensor and the safing sensor both indicate that a deployment crash event is occurring. Typically, a safing sensor is a directional inertia responsive switch or accelerometer.
10 Consequently, separate safing sensors are required for each crash sensor, which increases the cost of a restraint system proportional to the number of safing sensors being used.

Summary of the Invention

15 One aspect of the present invention provides a system for helping protect a vehicle occupant. The system includes a crash sensor operative to sense a vehicle crash event and to provide a crash signal having a characteristic indicative of the sensed crash
20 event. An acoustic safing sensor is operative to sense acoustic waves within the vehicle during a vehicle crash event and provide a safing signal having a characteristic indicative of the sensed acoustic waves. The system also includes an actuatable occupant

protection device for, when actuated, helping protect the vehicle occupant during a vehicle crash event. A controller controls actuation the occupant protection device in response to both the crash signal and the
5 safing signal indicating a vehicle crash event.

Another aspect of the present invention provides a system for helping to protect a vehicle occupant. The system includes a plurality of crash event sensors, each being operative to sense a different condition of
10 the vehicle and to provide a corresponding sensor signal having a characteristic indicative of the vehicle condition sensed thereby. An acoustic safing sensor is operative to detect acoustic waves within the vehicle during a vehicle crash event and to provide a
15 safing signal having a characteristic indicative of the sensed acoustic waves. The system also includes an occupant protection device which, when actuated, helps protect the vehicle occupant during a vehicle crash event. A controller is connected with each of the
20 crash event sensors, the acoustic sensor, and the occupant protection device. The controller controls actuation of the occupant protection device in response to the sensor signal from any one of the crash event

sensors and the safing signal from said acoustic sensor.

Still another aspect of the present invention provides a system for helping to protect a vehicle
5 occupant. The system includes a sensor module mountable in a vehicle. The sensor module includes an accelerometer operative to sense vehicle acceleration and to provide an acceleration signal having a
characteristic indicative of the sensed vehicle
10 acceleration. The sensor module further includes an acoustic sensor operative to sense acoustic waves of the vehicle during a vehicle crash event and to provide a safing signal having a characteristic indicative of
the sensed acoustic waves. The system includes an
15 occupant protection device which, when actuated, helps protect the vehicle occupant during a vehicle crash event. A controller controls actuation of the occupant protection device in response to both the acceleration signal and the safing signal.

20 Yet another aspect of the present invention provides a method for controlling actuation of an actuatable occupant protection device of a vehicle. The method includes the steps of sensing a vehicle crash condition and providing an crash event signal

having a characteristic indicative of the sensed vehicle crash condition. Acoustic waves traveling through the vehicle are sensed and a safing signal is provided based on the sensed acoustic waves. The occurrence of a vehicle crash event is determined in response to the crash event signal and the safing signal and actuation of an occupant protection device is controlled in response to such determination.

Brief Description of the Drawings

The foregoing and other features and advantages of the invention will become more apparent to one skilled in the art upon consideration of the following description of the invention and the accompanying drawings in which:

Fig. 1 is a schematic block diagram of a vehicle equipped with a system in accordance with the present invention;

Fig. 2 is a functional diagram illustrating the operation of the system shown in Fig. 1 in accordance with the present invention.

Fig. 3 is a schematic block diagram of a vehicle equipped with a system in accordance with another exemplary embodiment of the present invention; and

Fig. 4 is a schematic block diagram of a vehicle equipped with a system in accordance with yet another exemplary embodiment of the present invention.

Description of an Exemplary Embodiment

5 Fig. 1 illustrates an actuatable occupant restraint system 10 for use in a vehicle 12. The vehicle 12 includes driver side and passenger side seats 14 and 16, respectively. The restraint system 10 includes at least one and preferably a plurality of
10 actuatable restraint devices 18, 20, and 22 associated with the driver side seat 14. One or more actuatable restraint devices 24, 26, and 28 also are associated with the passenger seat 16.

 By way of example, as shown in Fig. 1, a frontal
15 inflatable restraint device 18, a side inflatable restraint device 20 as well as a seat belt pretensioner device 22 are associated with the drivers side seat 14. Similarly, a frontal inflatable restraint device 24, a side inflatable restraint device 26 and a seat belt
20 pretensioner device 28 are associated with the passenger seat 16. Other types of actuatable occupant protection devices also may be associated with each seat 14, 16, such as an inflatable seat belt, an inflatable knee bolster, and an actuatable head

restraint. The frontal air bags 18 and 24 also may be single stage or multi-stage inflatable restraint devices.

5 The restraint system 10 further includes a
controller 30 electrically coupled to each of the
actuatable occupant protection devices 18, 20, 22, 24,
26, 28 for controlling actuation of each of the
actuatable occupant protection devices. The
10 controller 30 preferably is a microcomputer programmed
to control actuation of the occupant protection
devices. The functionality of the controller 30
alternatively could be performed by one or more digital
and/or analog circuits. The controller 30 also may be
embodied in an application specific integrated circuit.

15 The controller 30 controls actuation of the
occupant protection devices 18, 20, 22, 24, 26, and 28
upon determining the occurrence of a vehicle crash
event. The controller 30 makes this determination in
response to input signals received from a plurality of
20 crash event sensors 32, 34, 36, 38, and 40 located in
the vehicle 12.

Each of the crash sensors 32, 34, 36, 38, 40
monitors a particular vehicle condition and is
responsive to the occurrence of a vehicle crash event.

Each crash sensor 32, 34, 36, 38, 40 provides a crash signal having an electrical characteristic indicative of the vehicle condition sensed thereby. The system 10 preferably includes a crash sensor module 42 in which

5 at least two different types of crash sensors are located, namely sensors 32 and 34. The crash sensor module 42 has a housing, which may be located at a central location in the vehicle 12 (Fig. 1).

For example, the crash sensor 32 is an

10 accelerometer (or a plurality of accelerometers) that senses vehicle acceleration along one or more axes extending through the vehicle 12. The crash sensor 32 provides an acceleration signal to the controller 30 having an electrical characteristic that is indicative

15 of the sensed vehicle acceleration, or deceleration, along its axis (or axes) of sensitivity.

The crash sensing device 34 is an acoustic transducer, such as an ultrasonic sensor, mounted to the vehicle 12. The crash sensing device senses high

20 frequency acoustic waves that propagate through the vehicle structure during the occurrence of a vehicle crash event. For simplicity of explanation, and not by way of limitation, the "crash sensor 34" is hereinafter referred to as the "ultrasonic sensor 34." The

ultrasonic sensor 34 converts the sensed acoustic waves into a signal having an electrical characteristic indicative of the acoustic waves or vibrations transmitted through the vehicle during a vehicle crash event.

The ultrasonic sensor 34, for example, is a microphone, mounted within the housing of sensor module 42. The ultrasonic sensor 34 preferably is mounted to a printed circuit board (not shown) to which the crash sensor 32 also is mounted. In particular, the ultrasonic sensor 34 is connected with the vehicle frame, either directly or indirectly through intervening components, such as the printed circuit board and/or housing of the sensor module 42.

The sensors 36, 38, and 40 are crush zone sensors mounted respectively at the radiator location of the vehicle 12 and along the doors or B-pillars of the vehicle. The crush zone sensors 36, 38, and 40 enable the controller 30 to better discriminate between certain types of vehicle crash event conditions. Each of the crush zone sensors 36, 38, 40, for example, provides a signal to the controller 30 having an electrical characteristic functionally related to the crash acceleration experienced by the portion of the

vehicle to which the sensor is mounted. Alternatively, the sensors 36, 38, and 40 may provide a signal indicating that an associated part of the vehicle has been deformed by at least a predetermined amount. In this way, the controller 30 can better determine the location of impact and/or the severity thereof.

The operation of the system 10 of Fig. 1 will be better appreciated with respect to Fig. 2, in which identical reference numbers refer to corresponding parts of the system 10 previously identified with respect to Fig. 1. The blocks located with the controller 30 indicate functions performed by the controller. Additionally, while, for purposes of simplicity of explanation, Fig. 2 shows the controller 30 connected to control actuation of three occupant protection devices 18, 20, and 22 associated with the driver seat 14 (Fig. 1), the controller functions are equally applicable to the occupant protection devices 24, 26, and 28 associated with the passenger seat 16 (Fig. 1) or other locations in the vehicle. Such controller functions are also applicable to control actuation of other types of restraint devices that may be used in the system 10.

The crash sensor module 42 houses the ultrasonic sensor 34 and the crash sensor 32. The crash sensor 32 includes an X-accelerometer 50 and a Y-accelerometer 52. The X-accelerometer 50 and the Y-accelerometer 52 are oriented so as to have substantially transverse axes of sensitivity. The X-accelerometer 50, for example, is operative to sense vehicle acceleration along an X-axis oriented parallel to the direction of travel of the vehicle. The Y-accelerometer 52 has an axis of sensitivity oriented transverse to the direction of travel of the vehicle, e.g., a Y-axis. The Y-accelerometer 52, for example, may sense vehicle acceleration along a lateral (e.g., side to side) or vertical direction of the vehicle.

Each of the accelerometers 50, 52 provides a respective acceleration signal having an electrical characteristic indicative of the vehicle acceleration sensed thereby. The acceleration signals can take any of several forms known in the art. The crash acceleration signals, for example, can have amplitude, frequency, pulse duration, and/or other characteristics that vary as a function of the sensed acceleration.

The X-accelerometer 50 provides its acceleration signal to an analog amplifier 54 which amplifies the

acceleration signal to a useable level. The amplifier 54, in turn, provides an amplified acceleration signal to an analog filter network 56, which also may be connected to the same PC board and be
5 located in the sensor module 42. The filter network 56 removes undesired frequency components and noise that are not helpful in determining the occurrence of a vehicle crash event. The filter network 56 provides an amplified, filtered signal to an input of the
10 controller 30 via connection 57.

The acceleration signal from the Y-accelerometer 52 also is amplified and filtered through a corresponding amplifier 58 and filter network 60. The filter network 60 provides an amplified, filtered
15 signal to another input of the controller 30 via connection 61.

The signal from the ultrasonic sensor 34 is amplified to a useable level by an appropriate analog amplifier 62. The amplified signal is provided to an
20 envelope detector 64 formed of an analog filter network. The envelope detector, for example, includes a bandpass filter ("BP") 66 and a high-pass ("HP") filter 68 to respectively provide envelope detection and help remove drift. Other circuitry could be used

for providing the desired envelope detection of the ultrasonic waves that propagate through the vehicle structure. The amplifier 62 and the filter network 64 are schematically illustrated as being connected to a common circuit board located within the housing of the sensor module 42. The filter network alternatively could be located external to the module.

The ultrasonic sensor 34 and analog filter network 64 are designed or tuned to be responsive to ultrasonic acoustic waves traveling through the vehicle within a selected frequency range. In particular, the ultrasonic sensor 34 is responsive to acoustic waves traveling through the vehicle structure at about 200 to about 300 kHz, which is the resonant frequency of a vehicle body during a vehicle crash event. The frequency range could be broader or narrower, as desired. The high-pass filter 68 provides a filtered signal to a corresponding input of the controller 30 via connection 70.

The analog crash sensor signals provided at lines 57, 61 and 70 from the respective crash sensors 50, 52, and 34 are converted to corresponding digital signals through respective analog-to-digital (A/D) converters 72, 74, and 76. The A/D

converters 72, 74, and 76 may be part of the controller 30, as shown, or may be part of other circuitry located external to the controller. Each A/D converter 72, 74, 76 provides a digitized

- 5 representation of the respective input signals, as is known in the art. The digitized crash sensor signals, indicated at 78, 80, and 82, are, in turn, filtered through appropriate digital filter functions 84, 86, and 88, respectively, performed by the controller 30.
- 10 The digital filter functions 84 and 86, for example, may include high pass and/or low pass digital filtering for removing unwanted frequency components. The filter functions 84 and 86 also may integrate the crash sensor signals. The filter functions 84 and 86
- 15 provide digitized filtered signals 90 and 92, respectively, to a crash discrimination function 94.

- The crash discrimination function 94, for example, is a software module stored in the controller 30 that discriminates between deployment and non-deployment
- 20 crash events. The crash discrimination function 94 also may determine the severity of the detected crash event based on the crash sensor signals from each of the accelerometers 50 and 52, the signals from the crush zone sensors 36, 38, and 40, and signals provided

from other sensors 96. For example, crash severity may be determined to help control actuation of a multi-stage actuatable occupant protection device, such as one or more of the inflatable restraint devices 18, 20, 24, and 26 (Fig. 1).

Referring back to Fig. 2, the crash discrimination function 94 further may determine crash severity based on a digitized ultrasonic sensor signal 82 from the A/D converter 76. In particular, crash severity may be determined as a function of the amplitude of the digitized ultrasonic sensor signal 82 over time or, alternatively, as a function of the energy of the digitized ultrasonic signal. Using the ultrasonic sensor signal 82 advantageously permits a rapid determination of crash severity, as it does not rely on moving parts to be actuated.

The other sensors 96, which may form part of the restraint system 10 in accordance with the present invention, may detect a condition of a vehicle occupant located in the vehicle seats 14 and 16 (Fig. 1). The occupant conditions may include occupant weight, occupant position within the vehicle, whether the occupant is belted, etc. Each of such other sensors 96 provides a sensor signal 98 to an A/D converter 100 of

the controller 30. The A/D converter 100, in turn, provides a digitized indication of the sensed condition, indicated at 102, to the crash discrimination function 94. Appropriate filtering also
5 may be provided, but has been omitted for simplicity of explanation. The signal 102 further may be used by the crash discrimination function 94 to help control actuation of the actuatable occupant protection devices 18, 20, 22, 24, 26, and 28 (Fig. 1).

10 An example of one type of crash severity algorithm that can be used in the crash discrimination function 94 is of the type disclosed in U.S. patent application serial number 09/197,143 to Foo et al., filed November 20, 1998, entitled "Method and Apparatus
15 for Controlling an Actuatable Restraint Device Using Crash Severity Indexing and Crush Zone Sensor." Briefly stated, the crash discrimination is performed by a crash severity algorithm. The crash severity algorithm provides a signal having several features for
20 controlling actuation of the associated occupant protection devices 18, 20, and 22. One feature, for example, indicates that a deployment crash condition is occurring and is used to actuate the first stage of a multi-stage actuatable occupant protection device, such

as the frontal air bag 18. Other features of the crash severity signal are used, for example, to control actuation of other stages of the multi-stage restraint device 18 as well as control actuation of other

5 occupant protection devices of the system, such as devices 20 and 22. Other types of crash algorithms and methods of crash discrimination also may be used with the present invention.

Referring back to Fig. 2, the crash discrimination

10 function 94 provides signals 104, 106, and 108 for controlling actuation of the respective occupant protection devices 18, 20, and 22. Specifically, each of the crash discrimination signals 104, 106, 108 is provided to a corresponding input of an associated AND

15 gate 110, 112, 114. Each of the AND gates has at least another input that receives a safing signal 116 from a common safing function 118.

The safing function 118 provides the safing signal 116 as a function of the digitized ultrasonic

20 sensor signal 82. The safing function 118 includes the digital filter function 88. The digital filter function 88 provides a filtered, digitized signal 122 to an input of a comparator function 124. The safing function 118 also includes a threshold circuit 126 that

provides a predetermined reference signal 128 to another input of the comparator function 124.

The comparator function 124 compares the filtered, digitized sampling of the ultrasonic signal 122 against the reference signal 128 to provide the safing signal 116 indicative of the occurrence or non-occurrence of a vehicle crash event. In particular, the comparator provides the safing signal 116 at a first logic level (e.g., HIGH) when the signal 122 has a value that is greater than the reference signal 128. On the other hand, if the signal 122 has a value that is less than or equal to the reference signal 128, the safing signal 116 is provided at another logic level (e.g., LOW).

The filter function 88 performs signal processing on the signal 88 to provide the signal 122 having characteristics commensurate with the reference signal 128 being provided by the threshold circuit 126. The filter function 88, for example, may be a digital filter having a transfer function with a low time constant so as to provide a time-averaged representation of the ultrasonic sensor signal. Alternatively or additionally, the filter function 88 may integrate the sampled sensor signal 82 with respect

to time to provide a signal having a characteristic indicative of the measured energy of the sensed acoustic waves over time. For example, the signal 122 is in the form of a window that includes a plurality of digitized samples indicative of the sensed acoustic waves traveling through the vehicle over time. The filtered signal 122 also may be provided to the crash discrimination function 94 to help discriminate between different types of crash events.

Similarly, the threshold circuit 126 is configured to provide the reference signal 128 according to the particular signal parameters contained in the filtered signal 122. The reference signal 128, for example, may be a reference voltage level of a predetermined amplitude to provide a fixed threshold. The particular amplitude of the reference signal preferably is normalized to a level suitable for comparison with the reference signal 128. The normalization will vary depending on the part of the vehicle to which the ultrasonic sensor 34 is mounted and the particular medium (e.g., the sensor module housing and other vehicle structure) through which the ultrasonic signals must propagate to reach the ultrasonic sensor. Furthermore, rather than a fixed threshold reference

signal 128, the threshold circuit 126 may be configured to provide a variable reference signal that varies with respect to time, such as based on empirical data obtained for a particular vehicle platform.

5 The comparator function 124 compares the threshold signal 128 and the filtered ultrasonic signal 122 to provide the safing signal 116 (e.g., logic LOW or HIGH). The safing signal 116 is logically ANDed with each of the crash discrimination signals 104, 106, 108
10 from the crash discrimination function 94. Provided that the safing signal 116 indicates that a vehicle crash event is occurring (e.g., logic HIGH), appropriate crash signals 130, 132, and 134 are provided to the respective occupant protection devices,
15 such as the front air bag 18, the seat belt pretensioner device 22, and the side air bag 20. In accordance with the present invention, the safing signal 116 also is used to provide safing for the other occupant protection devices 24, 26, and 28 associated
20 with the passenger seat 16 (Fig. 1).

While the safing function 118 has been described as processing the ultrasonic sensor signal based on the amplitude thereof, other aspects of the ultrasonic sensor signal may be used and processed to provide the

safing signal 116. For example, the frequency, energy, and/or an integration of the ultrasonic sensor signal may be algorithmically processed to provide an indication of the occurrence and/or of the severity of a vehicle crash event. The crash discrimination function 94 also might use the digitized ultrasonic signal 82 to help discriminate the occurrence of a vehicle crash event and/or determined the severity thereof.

Fig. 3 illustrates an alternative exemplary embodiment of an actuatable occupant protection system 210 mounted in a vehicle 212. The system 210 includes a central crash sensing module 214 mounted in a substantially central vehicle location. The central module 214 includes a controller, such as a microcomputer, for determining the occurrence of a deployment vehicle crash event and controlling actuation of appropriate occupant protection equipment. In order to detect the occurrence of a vehicle crash event, the crash sensing module 214 includes an acceleration sensor 216 for sensing vehicle crash acceleration. By way of example, the acceleration sensor 216 is an accelerometer that senses vehicle acceleration along an X-axis of the vehicle 212

extending between the front and rear ends of the vehicle. The central module 214 also includes an ultrasonic sensor 218. The ultrasonic sensor 218 is an omni-directional ultrasonic sensing device

5 substantially identical to that described above with respect to Figs. 1 and 2.

The system 210 includes actuatable vehicle occupant protection equipment for helping protect vehicle occupants during determined deployment crash

10 events. For example, the system 210 includes front air bags 220 and 222 and side air bags 224 and 226. Seat belt pretensioner devices (not shown for purposes of brevity) also could be part of the system 210 associated with respective vehicle seats 219 and 221.

15 The system 210 includes side impact crash sensors 228 and 230 located at side locations of the vehicle remote from the central module 214. The side impact crash sensors 228 and 230 are connected to the central module 214. For example, side impact crash sensors 228

20 and 230 are acceleration sensors (e.g., accelerometers) for sensing acceleration of the side part of the vehicle to which each sensor is mounted. Each such accelerometer detects acceleration of a side part of

the vehicle along a Y-axis, which extends laterally through the vehicle perpendicular to the X-axis.

In this exemplary embodiment, no Y-axis accelerometer is required within the central module 214
5 for safing side impact vehicle crash events. Instead, the ultrasonic sensor 218 provides omni-directional safing for both frontal vehicle crash events (e.g., sensed by acceleration sensor 216) and side impact crash events (e.g., sensed by side impact sensors 228,
10 230). Accordingly, the controller of the central module 214 controls actuation of the associated occupant protection equipment in response to the acoustic waves detected by the ultrasonic sensor 218 and the vehicle acceleration detected by the
15 acceleration sensor 216 and/or the remote crush zone sensors 228, 230.

The omni-directional ultrasonic sensor 218 helps improve the time-to-fire during the frontal impact crash events without the need for a front crush zone
20 sensor (e.g., 36 of Fig. 1). The responsiveness and, thus, time-to-fire characteristics for side impact crash events also are improved through the use of the ultrasonic safing sensor 218 in combination with the side impact sensors 228 and 230.

Fig. 4 illustrates yet another exemplary embodiment of an actuatable occupant protection system 310 mounted in a vehicle 312. This system 310 includes a central module 314 mounted at a central location within the vehicle 312. In this exemplary embodiment, the central module 314 includes a controller, such as a microcomputer programmed for determining the occurrence of a vehicle crash event and for controlling actuation of associated occupant protection equipment.

The central module 314 includes an ultrasonic sensor 316, such as described with respect to the embodiment of Figs. 1 and 2. The system 310 includes a front vehicle crash event sensor 318 connected with the central module 314. The front crash event sensor 318 is located in forward part of the vehicle 312 remote from the central module 314. The system 310 also includes side impact crash event sensors 320 and 322 connected with the central module 314. The side impact crash sensors are located at the respective sides of the vehicle 312 remote from the central module 314.

By way of example, the front crash sensor 318 preferably is a crush zone sensor, such as an accelerometer having an axis of sensitivity along an X-axis that extends between the front and rear ends of

the vehicle 312. The side impact crash sensors 320 and 322 also are crush zone sensors, but have axes of sensitivity oriented along a Y-axis of the vehicle 312, which extends laterally through the vehicle

5 substantially perpendicular to the X-axis. Each of the crash sensors 318, 320, 322 provides a signal to the central module 314 having an electrical characteristic indicative of the acceleration sensed thereby.

10 The ultrasonic sensor 316, as mentioned above, operates as an omni-directional crash event sensor. That is, the ultrasonic sensor 316 detects acoustic waves or vibrations transmitted through the vehicle during a vehicle crash event originating from any direction.

15 The central module 314 controls actuatable occupant protection devices associated with vehicle seats 323, 325. The system 310 includes, for example, front air bags 324 and 326 and side air bags 328 and 330. Seat belt pretensioners as well as other occupant
20 protection equipment also may, in accordance with the present invention, be used in the system 310 and be controlled by the central module 314.

The central module 314 is programmed to discriminate between deployment and non-deployment

front impact crash events and deployment and non-deployment side impact crash events. The central module 314 controls actuation of the associated occupant protection equipment (e.g., 324, 326, 328, 330) in response to the acoustic waves detected by the ultrasonic sensor 316 and vehicle acceleration detected by the remote crash sensors 318, 320, 322. The ultrasonic sensor 316 provides omni-directional safing for each of the crash event sensors 318, 320, 322. The ultrasonic sensor 316 also provides an additional mechanism for helping to discriminate between deployment and non-deployment vehicle crash events. This, in turn, helps to improve system responsiveness and time-to-fire characteristics for deployment crash events.

In view of the foregoing, the system (e.g., 10, 210, 310), in accordance with present invention, provides a method and apparatus for controlling actuation of one or more occupant protection devices with a common ultrasonic sensor (e.g., 34, 218, 316) that verifies the occurrence of a vehicle crash event. Advantageously, the ultrasonic sensor has a virtually instantaneous response time, substantially only limited

by the speed of sound and the attenuation of the signal in the vehicle body.

In addition, the ultrasonic sensor (e.g., 34, 218, 316) is able to sense acoustic waves or vibrations

5 traveling through the vehicle due to the occurrence of a vehicle crash event, regardless of the direction of impact and the cause of the impact, except perhaps an impending vehicle rollover condition. Therefore, a

single ultrasonic sensor, in accordance with the present invention, provides an omni-directional safing 10 sensor for use in combination with a plurality of occupant protection devices that may be actuated in response to sensing different vehicle conditions

indicative of a vehicle crash event. Accordingly, the use of an omni-directional ultrasonic sensor further 15 reduces manufacturing costs typically associated with having more than one safing sensor.

Furthermore, using the ultrasonic sensor as a crash severity indicator may permit an earlier time-to- 20 fire determination than typically available with a conventional mechanical safing mechanism. This is particularly desirable in an occupant protection system having multi-stage occupant protection devices.

From the above description of the invention, those skilled in the art will perceive improvements, changes and modifications. Such improvements, changes and modifications within the skill of the art are intended to be covered by the appended claims.

5

Having described the invention, the following is claimed:

1. A system for helping to protect a vehicle occupant, said system comprising:

a crash sensor operative to sense a vehicle crash event and provide a crash signal having a characteristic indicative of the sensed crash event;

an acoustic safing sensor operative to sense acoustic waves of the vehicle during a vehicle crash event and provide a safing signal having a characteristic indicative of the sensed acoustic waves;

an actuatable occupant protection device for, when actuated, helping to protect the vehicle occupant during a vehicle crash event; and

a controller which controls actuation of said occupant protection device in response to both said crash signal and said safing signal.

2. A system as set forth in claim 1 wherein said crash sensor is an accelerometer.

3. A system as set forth in claim 2 further including a sensor module mountable within a vehicle, said sensor module including said acoustic sensor and said accelerometer.

4. A system as set forth in claim 2 wherein said acoustic sensor is an omni-directional ultrasonic sensor for sensing ultrasonic acoustic waves of the vehicle during vehicle crash events originating in any of a plurality of directions and providing said safing signal indicative thereof.

5. A system as set forth in claim 4 further including a sensor module mountable within a vehicle, said ultrasonic sensor being part of said sensor module, said accelerometer being a crush zone sensor remote from said sensor module for sensing vehicle acceleration of part of the vehicle indicative of a vehicle crash event and providing said crash signal having an electrical characteristic indicative thereof.

6. A system as set forth in claim 5 wherein said crush zone sensor is a front crush zone sensor located at a forward part of the vehicle and electrically

connected with said controller, said front crush zone sensor sensing a front impact vehicle crash event in response to movement of the forward part of the vehicle and providing a front crash signal indicative thereof, said controller controlling actuation of said occupant protection device in response to both said safing signal and said front crash signal.

7. A system as set forth in claim 5 wherein said crush zone sensor is a side crush zone sensor located at a side part of the vehicle and electrically connected with said controller, said side crush zone sensor sensing a side impact vehicle crash event in response to movement of the side part of the vehicle and providing a side crash signal indicative thereof, said controller controlling actuation of said occupant protection device in response to both said safing signal and said side crash signal.

8. A system as set forth in claim 1 wherein said crash sensor further includes a plurality of accelerometers, each of said plurality of accelerometers being operative to sense vehicle acceleration and provide a respective acceleration

signal, said controller controlling actuation of said occupant protection device in response to an acceleration signal from at least one of said plurality of accelerometers and said safing signal, whereby the acoustic safing sensor provides an omni-directional safing sensor for each of the plurality of accelerometers.

9. A system as set forth in claim 8 further including a sensor module mountable within a vehicle, said acoustic sensor and at least one of said plurality of accelerometers being part of said sensor module.

10. A system for helping to protect a vehicle occupant, said system comprising:

a plurality of crash event sensors, each of said plurality of crash event sensors being operative to sense a different condition of the vehicle and to provide a corresponding sensor signal having a characteristic indicative of the vehicle condition sensed thereby;

an acoustic sensor operative to sense acoustic waves of the vehicle during a vehicle crash

event and to provide a safing signal having a characteristic indicative of the sensed acoustic waves;

an occupant protection device for, when actuated, helping to protect the vehicle occupant during a vehicle crash event; and

a controller connected with each of said plurality of crash event sensors, said acoustic safing sensor, and said occupant protection device, said controller determining the occurrence of a vehicle crash event and controlling actuation of said occupant protection device in response to the sensor signal from any one of said plurality of crash event sensors and the safing signal from said acoustic sensor, whereby the acoustic sensor provides omni-directional safing for the plurality of crash event sensors.

11. A system as set forth in claim 10 wherein each of plurality of said crash event sensors is selected from a group consisting of an accelerometer and a crush zone sensor.

12. A system as set forth in claim 10 further including a sensor module mountable within a vehicle, said acoustic sensor being part of said sensor module.

13. A system as set forth in claim 12 wherein said at least one of said plurality of crash event sensors is part of said sensor module.

14. A system for helping to protect a vehicle occupant, said system comprising:

a sensor module for mounting in a vehicle, said sensor module including:

an accelerometer operative to sense vehicle acceleration and provide an acceleration signal having a characteristic indicative of the sensed vehicle acceleration; and

an acoustic sensor operative to detect acoustic waves of the vehicle during a vehicle crash event and to provide a safing signal having a characteristic indicative of the sensed acoustic waves;

an occupant protection device for, when actuated, helping to protect the vehicle occupant during a vehicle crash event; and

a controller which controls actuation of said occupant protection device in response to both said acceleration signal and said safing signal.

15. A system as set forth in claim 14 wherein said sensor module further includes a plurality of accelerometers, each of said plurality of accelerometers being operative to sense vehicle acceleration and provide a respective acceleration signal indicative of the vehicle acceleration sensed thereby, said controller controlling actuation of said occupant protection device in response to the acceleration signal from at least one of said plurality of accelerometers and said safing signal from said acoustic sensor, whereby the acoustic sensor provides omni-directional safing for the plurality of accelerometers.

16. A system as set forth in claim 14 further including a side crush zone sensor located at a side part of the vehicle and electrically connected with said controller, said side crush zone sensor sensing a side impact vehicle crash event in response to acceleration of the side part of the vehicle and providing a side crash signal indicative thereof, said controller controlling actuation of said occupant protection device in response to both said safing signal and said side crash signal.

17. A method for controlling actuation of an actuatable occupant protection device of a vehicle, said method comprising the steps of:

sensing a vehicle crash condition;

providing an crash event signal having a characteristic indicative of the sensed vehicle crash condition;

sensing acoustic waves that travel through the vehicle in response to the occurrence of the vehicle crash condition;

providing a safing signal having a characteristic indicative of the sensed acoustic waves during the vehicle crash condition;

determining the occurrence of a vehicle crash event in response to the crash event signal and the safing signal indicating a vehicle crash condition; and

controlling actuation of an occupant protection device in response to said determination.

18. A method as set forth in claim 17 further including providing a plurality of crash event sensors, each of the crash event sensors sensing a vehicle crash condition and providing a crash event signal indicative

of the vehicle crash condition sensed thereby, said step of determining a vehicle crash event further including determining the occurrence of a vehicle crash event in response to the crash signal from at least one of the plurality of crash event sensors and the safing signal from the acoustic sensor, whereby the safing signal provides omni-directional safing for the plurality of crash event sensors.

19. A method as set forth in claim 18 wherein each crash sensor is an accelerometer that provides an acceleration signal indicative of vehicle acceleration.

20. A method as set forth in claim 17 further including mounting a front crush zone sensor at a forward part of the vehicle, said step of sensing a vehicle crash condition including sensing a front impact vehicle crash event with the front crush zone sensor, the crash event signal being a front crash signal indicative of the sensed front impact vehicle crash event sensed by the front crush zone sensor, actuation of the occupant protection device being controlled in response to both the safing signal and the front crash signal.

21. A method as set forth in claim 17 further including mounting a side crush zone sensor at a side part of the vehicle, said step of sensing a vehicle crash condition including sensing a side impact vehicle crash event with the side crush zone sensor, the crash event signal being a side crash signal indicative of the sensed side impact vehicle crash event sensed by the side crush zone sensor, actuation of the occupant protection device being controlled in response to both the safing signal and said the crash signal.

22. A system for helping to protect a vehicle occupant, said system comprising:

means for sensing a vehicle crash condition and providing an crash event signal having a characteristic indicative thereof;

means for sensing acoustic waves that travel through the vehicle in response to the occurrence of the vehicle crash condition and providing a safing signal having a characteristic indicative thereof; and

control means for determining the occurrence of a vehicle crash event in response to the crash event signal and the safing signal and controlling actuation


of an occupant protection device in response to the determination.

104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239
2240
2241
2242
2243
2244
2245
2246
2247
2248
2249
2250
2251
2252
2253
2254
2255
2256
2257
2258
2259
2260
2261
2262
2263
2264
2265
2266
2267
2268
2269
2270
2271
2272
2273
2274
2275
2276
2277
2278
2279
2280
2281
2282
2283
2284
2285
2286
2287
2288
2289
2290
2291
2292
2293
2294
2295
2296
2297
2298
2299

Abstract

A system (10) for helping to protect a vehicle occupant includes a crash sensor (32) operative to sense a vehicle crash event and provide a crash signal having a characteristic indicative of the sensed crash event. An acoustic safing sensor (34) is operative to sense acoustic waves of the vehicle during a vehicle crash event and provide a safing signal having a characteristic indicative of the sensed acoustic waves.

The system (10) also includes an occupant protection device (18, 20, 22, 24, 26, 28) for, when actuated, helping to protect the vehicle occupant during a vehicle crash event. A controller (30) controls actuation of the occupant protection device (18, 20, 22, 24, 26, 28) in response to the crash signal and the safing signal.







Fig.2






Fig. 4

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

Atty. Docket No. TRW(TE)4170

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled **METHOD AND APPARATUS FOR CONTROLLING AN ACTUATABLE OCCUPANT PROTECTION DEVICE USING AN ULTRASONIC SENSOR**, the specification of which:

(check one) ☒ is attached hereto.☐ was filed on _____ as Application Serial No. _____
and was amended on _____ (if applicable).☐ was filed on _____ as International Application No. _____
and was amended on _____
by ☐ Preliminary Amendment ☐ Article 19; ☐ Article 34 (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 or §365 of any foreign application(s) for patent or inventor's certificate or §365 of any PCT international application(s) designating at least one country other than the United States of America, listed below and have also identified below any foreign application(s) for patent or inventor's certificate, or §365 any PCT international application(s) having a filing date before that of the application(s) of which priority is claimed:

Prior Foreign Application(s)

(Number)	(Country)	(Day/Month/Year Filed)	Priority Claimed <input type="checkbox"/> Yes <input type="checkbox"/> No
(Number)	(Country)	(Day/Month/Year Filed)	<input type="checkbox"/> Yes <input type="checkbox"/> No

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)	(Filing Date)	(Status-patented, pending, abandoned)
(Application Serial No.)	(Filing Date)	(Status-patented, pending, abandoned)

Power of Attorney: As a named inventor, I hereby appoint the following attorneys: Thomas L. Tarolli, Reg. No. 20,177; Robert B. Sundheim, Reg. No. 20,127; Calvin G. Covell, Reg. No. 24,042; Barry L. Tummino, Reg. No. 29,709; Paul E. Szabo, Reg. No. 30,429; James L. Tarolli, Reg. No. 36,029; Ronald M. Kachmark, Reg. No. 34,512; Richard S. Wesorick, Reg. No. 40,871; Maurice R. Salada, Reg. No. 26,502; Allan W. Voge, Reg. No. 28,127; and Gary L. Hermanson, Reg. No. 34,349; each with full powers of substitution and revocation to prosecute this application and transact all business in the United States Patent and Trademark Office connected therewith.

SEND CORRESPONDENCE TO: TAROLLI, SUNDHEIM, COVELL, TUMMINO & SZABO L.L.P.
1111 LEADER BLDG., 526 SUPERIOR AVENUE
CLEVELAND, OHIO 44114-1400
DIRECT TELEPHONE CALLS TO: BARRY L. TUMMINO, (216) 621-2234

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

1) Full name of sole or first inventor **ROGER A. MCCURDY**

Inventor's signature	Date
Residence TROY, MICHIGAN	Citizenship U.S.A.
Post Office Address 2193 NORMANDY, TROY, MICHIGAN 48098	Country OAKLAND

2) Full name of second inventor

Inventor's signature	Date
Residence	Citizenship
Post Office Address	Country